


26 403 KF2 VITALIO JOY SYSTEM 260 SHOWER SYSTEM WITH THERMOSTATIC MIXER FOR WALL MOUNTING



PRODUCT DESCRIPTION

- Colour: phantom black
- consisting of:
 - horizontal swivable 450 mm shower arm
 - exposed Precision thermostatic with Aquadimmer function
 - allows change between:
 - head shower Vitalio Joy 260
 - spray patterns: Rain, SmartRain, Jet
 - maximum flow rate (at 3 bar): 7 l/min
 - with ball joint
 - rotation angle $\pm 15^\circ$
 - hand shower Vitalio Joy 110 Massage
 - spray patterns: Rain, Massage, SmartRain
 - maximum flow rate (at 3 bar): 9.5 l/min
 - adjustable in height with gliding element
 - shower hose VitalioFlex Trend 1750 mm 1/2" x 1/2" (28 742)
 - maximum flow rate system (at 3 bar): 9.5 l/min
 - GROHE EcoJoy - Less water, perfect flow
 - GROHE TurboStat - compact cartridge with wax thermoelement
 - GROHE SafeStop safety button at 38°C
 - GROHE SafeStop Plus optional temperature limiter at 43°C included
 - GROHE CoolTouch - no risk of scalding
 - GROHE ProGrip - with knurl structure
 - GROHE DreamSpray - perfect spray pattern
 - GROHE SprayDimmer - stepless flow rate adjustment
- Flexible Installation - 1 adjustable bracket for existing drill holes
- Inner WaterGuide - inner insulation for surface protection
- GROHE SpeedClean - effortless limescale removal
- TwistStop - to prevent hose from twisting
- suitable for instantaneous heaters from 18 kW/h
- minimum flow rate 5 l/min
- Consumer edition