

Technical drawing of the Doro 3000 shower set, showing three views: a side view, a front view, and a top view. The dimensions are as follows:

- Side View:**
 - Overall width: 417-447
 - Height of shower head: 133
 - Height of shower arm: 80
 - Height of shower head (top view): 181
 - Height of shower arm (top view): 1500
 - Height of shower head (side view): 15
- Front View:**
 - Height of shower head: 133
 - Height of shower arm: 80
 - Height of shower head (top view): 181
 - Height of shower arm (top view): 1500
 - Height of shower head (side view): 15
- Top View:**
 - Height of shower head: 133
 - Height of shower arm: 80
 - Height of shower head (top view): 181
 - Height of shower arm (top view): 1500
 - Height of shower head (side view): 15

- Colour: moon white/chrome
- consisting of:
- exposed/concealed SmartControl thermostat
- allows change between:
- head shower Rainshower Duo 360 with horizontal 450 mm shower arm, spray plate white
- GROHE PureRain/GROHE Rain O² spray* and TrioMassage
- maximum flow rate (at 3 bar): 21 l/min
-
- maximum flow rate (at 3 bar): 7.5 l/min
- hand shower wall holder (27 055)
- Silverflex shower hose 1500 mm 1/2" x 1/2" (28 364)
- minimum flow rate 10 l/min
- GROHE DreamSpray perfect spray pattern
- GROHE Long-Life finish
- GROHE CoolTouch no risk of scalding
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE Water Saving - Less water, perfect flow
- GROHE SafeStop safety button at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C included
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to Full Flow
- GROHE EasyReach shower tray
- SpeedClean anti-limescale system
- Inner WaterGuide for a longer life
- TwistStop to prevent hose from twisting
- requires rough-in set 26 264 and concealed unit 26 449 – all to be ordered separately
- * to be decided at first installation; factory default setting: GROHE PureRain
- GROHE Long-Life finish