



## 26 979 243 1 TEMPESTA SYSTEM 250 FLEX SHOWER SYSTEM WITH DIVERTER FOR WALL MOUNTING



### PRODUCT DESCRIPTION

- Colour: Matte Black
- consisting of:
  - horizontal 390 mm shower arm, adjustable before installation
  - diverter allows change between hand shower, head shower or head shower with reduced flow
  - head shower Tempesta 250
  - 2 spray patterns (via diverter): Rain, SmartRain
  - maximum flow rate (at 3 bar): 7.5 l/min
  - head shower with black rear cover
  - with ball joint, rotation angle  $\pm 10^\circ$
  - hand shower Tempesta 110 (26 912)
  - 2 spray patterns: Rain, Jet
  - maximum flow rate (at 3 bar): 6.9 l/min
  - adjustable in height with gliding element
  - distance between diverter and upper bracket: 920 mm
  - shower hose Relexaflex 1500 mm 1/2" x 1/2"
  - shower hose Relexaflex 500 mm
- flexible installation: connection to faucet / wall union for water supply with 1/2" thread of the 500 mm shower hose
- GROHE SmartSwitch - easily rotate the dial to enjoy your preferred spray option
- GROHE DreamSpray - perfect spray pattern
- ShockProof silicone ring prevents damages caused by shower falling
- GROHE SpeedClean - effortless limescale removal
- Inner WaterGuide - inner insulation for surface protection
- suitable for instantaneous heaters from 18 kW/h
- maximum flow rate (at 3 bar): 7.5 l/min
- minimum flow rate 5 l/min
- min. recommended pressure 1.0 bar
- professional edition